

Eagle Draft Flex Hose

Specialty

Low Temp Water Suction Drafting Hose

Application: Suction side drafting, Dry Hydrant Connections, Trash pumps Construction and Mining, Solid Material Transfer Drafting from lakes, ponds, rivers, pools, wells, etc. during structural firefighting operations.

Tube: Cold Weather PVC

Reinforcement: Rigid PVC helix

Temperature: -22° to 140°F

Couplings: NH LH Female x NH RL Male OR Storz Couplings



Hose Features:

- Corrugated exterior for superior flexibility
- Smooth bore for unrestricted flow
- Lightweight and flexible in cold weather
- Clear sidewall permits visual check of material flow
- Weatherproof - highly resistant to ozone, salt water, and ultraviolet light
- External helix provides for easy drag

Couplings Features:

- Manufactured from aircraft grade 6061-T6 seamless extrusions, Black hardcoat anodized
- Long Handle Swivels are forged T6, attached with hard alloy aluminum piston
- Three rocker lugs on 1" thru 3-1/2" and four rocker lugs on 4" thru 6"
- Storz Fittings offered in 5" only



NH Couplings



STORZ Couplings



Note: Over flexing or repeated flexing of hose within 18" of fitting is a common cause of hose failure.

Liverpool Location ISO 9001:2015 Certified QMS by Intertek



Download the JGB® Mobile App



Click for directions:

New England Region
Liverpool, NY 13088
(315) 451-2770

Great Lakes Region
Cheektowaga, NY 14225
(716) 684-8224

Mid-Atlantic Region
Charlotte, NC 28273
(704) 588-9920

Midwest Region
St. Louis, MO 63111
(314) 256-0833

Gulf Coast Region
Pasadena, TX 77503
(281) 930-7777

Connect with us:



www.jgbhose.com