

Eagle Hot Tar & Asphalt Hose

Asphalt/tar Suction & Delivery Hose



Application: Specially designed hose for conveying hot tar and asphalt.

Tube: Special synthetic high oil, abrasion and heat resistant elastomer compound, black, smooth

Reinforcement: High tensile textile cord, steel wire helix

Cover: NBR, black, anti-static, smooth with cloth impression, high oil, heat, abrasion, weather and ozone resistant

Temperature: -22° to 356°F

Part #	ID	OD	Wall	WP	Burst	Bend Radius	Weight
	in	in	in	psi	psi	in	lbs/ft
014-0322-7290I	2	2.72	0.35 (±0.02)	145	580	10.04	1.8
014-0480-7290I	3	3.78	0.39 (±0.02)	145	580	14.96	2.9
014-0642-7290I	4	4.83	0.39 (±0.02)	145	580	20.08	3.9



Liverpool Location ISO 9001:2015 Certified QMS by Intertek

Download the JGB® Mobile App



Click for directions:

New England Region
Liverpool, NY 13088
(315) 451-2770

Great Lakes Region
Cheektowaga, NY 14225
(716) 684-8224

Mid-Atlantic Region
Charlotte, NC 28273
(704) 588-9920

Midwest Region
St. Louis, MO 63111
(314) 256-0833

Gulf Coast Region
Pasadena, TX 77503
(281) 930-7777

Connect with us:



www.jgbhose.com