

HydraFlex™ Hose

DOUBLE WALLED CORRUGATED METAL HOSE

Hose Master's T316 double-walled, spirally-welded corrugated metal hose. Specially designed to maintain extreme pressure and flexibility, Hydraflex™ is self-draining and generates minimal in-line turbulence.



Braids:

- T304 Single Braid
- T304 Double Braid
- *T316 Braid available upon request

Features:

- Extraflex™ comes in 1/4" to 1-1/2" Inside Diameters
- Working Pressures range from 1000 to 5800 psi
- Static minimum bend radius* ranges from 1.1" to 5.1"
- Weight ranges from 0.21 to 2.16 lbs. per foot

Notes:

- The minimum bend radius is measured from the centerline of the hose
- The working pressure decreases with temperature
- For rapid pressure fluctuations consult JGB



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Liverpool Location ISO 9001:2015 Certified QMS by Intertek

Click for directions:

New England Region
Liverpool, NY 13088
(315) 451-2770

Great Lakes Region
Cheektowaga, NY 14225
(716) 684-8224

Mid-Atlantic Region
Charlotte, NC 28273
(704) 588-9920

Midwest Region
St. Louis, MO 63111
(314) 256-0833

Gulf Coast Region
Pasadena, TX 77503
(281) 930-7777

Download the JGB® Mobile App



Connect with us:



www.jgbhose.com